

Datasheet



Item Code	0458D45S42
Product Nomenclature	BV/2 EM 8-0+S42 DG AS 4,5mm
Product Group	PVC-S
Belt Application	General Conveying, incline / decline application

<u>Product Construction</u>		<u>Technical Data</u>	
Type of fabric	EM (lateral stable)	Total Thickness	4,5 mm
Number of ply	2	Weight	4,1 kg/m ²
Fabric feature	Lateral Stiff	Temperature Tolerance	-10 to +80 Celsius
Conveying side		Coeff. Friction > Steel	0,2
Coating Material	PVC	Tensile Strength at 1% elongation	8 N/mm
Colour	Dark Green	Min. Pulley	60 mm
Hardness	45 Shore A	Product Characteristics	
Surface	Super grip, wavy	Troughed Installation suitable	No
Running Side		Oil resistant	No
Coating Material	Fabric	Permanent antistatic	Yes
Colour	-	FDA approved	No
Hardness	-	EC 10/2011	No
Surface	-	REACH	Yes
		Flame Retardant	No
		Standard Production Width	3000mm

<u>Fabrication Recommendation</u>				
Joining Temperature	Upper	180 Celsius	Heat preservation time	4 min
	Lower	175 Celsius	Pressure	2 bar
Welded Joints	Finger over Finger			

Disclaimer

All information are recommendations and believed to be reliable, but no representations, guarantees, or warranties of any kind are made as to their accuracy or suitability for particular applications. Due to the fact that Haggart Belting has no control of use, we will not assume any liability concerning the suitability and process ability of the products mentioned herein. This also applies to defects, damages, consequential damages, and other consequences. The information applies at approx. 20°C (68°F). Keep the belt tension to a minimum for maximum belt and conveyor life. Stated is the belt temperature. The allowable product temperature may vary.