

Datasheet



Item Code	0812B28S32-X
Product Nomenclature	BV/2 EX 10-0+S32 BK FR AS 2.8 mm
Product Group	PVC-S
Belt Application	Suitable for low noise application, incline / decline application; warehouse and airport

<u>Product Construction</u>		<u>Technical Data</u>	
Type of fabric	EX (low noise)	Total Thickness	3.0 mm
Number of ply	2	Weight	3,1 kg/m ²
Fabric feature	Lateral Stiff	Temperature Tolerance	-10 to +80 Celsius
<u>Conveying side</u>		Coeff. Friction > Steel	0,2
Coating Material	PVC	Tensile Strength at 1% elongation	10 N/mm
Colour	Black	Min. Pulley	50 mm
Hardness	60 Shore A	<u>Product Characteristics</u>	
Surface	S32: longitudinal grip	Troughed Installation suitable	No
<u>Running Side</u>		Oil resistant	No
Coating Material	Fabric	Permanent antistatic	Yes
Colour	-	FDA approved	No
Hardness	-	EC 10/2011	No
Surface	-	REACH	Yes
		Flame Retardant	Yes
		<u>Standard Production Width</u>	3000mm

<u>Fabrication Recommendation</u>				
<u>Jointing Temperature</u>	Upper	175 Celsius	<u>Heat preservation time</u>	4 min
	Lower	170 Celsius	<u>Pressure</u>	2 bar
<u>Welded Joints</u>	Finger over Finger			

Disclaimer

All information are recommendations and believed to be reliable, but no representations, guarantees, or warranties of any kind are made as to their accuracy or suitability for particular applications. Due to the fact that Haggart Belting has no control of use, we will not assume any liability concerning the suitability and process ability of the products mentioned herein. This also applies to defects, damages, consequential damages, and other consequences. The information applies at approx. 20°C (68°F). Keep the belt tension to a minimum for maximum belt and conveyor life. Stated is the belt temperature. The allowable product temperature may vary.