

Datasheet



Item Code	0131R64S32
Product Nomenclature	BV/2 EM8 0+S32 Red AS 6.4mm
Product Group	PVC
Belt Application	Incline, Case sealers

<u>Product Construction</u>		<u>Technical Data</u>	
Type of fabric	EM (Polyester)	Total Thickness	6.4mm
Number of ply	2	Weight	5.6 kg/m ²
Fabric feature	Lateral Stiff	Temperature Tolerance	-10 to +90 Celsius
<u>Conveying side</u>		Coeff. Friction > Steel	0,2
Coating Material	PVC	Tensile Strength at 1% elongation	8 N/mm
Colour	Red	Min. Pulley	50 mm
Hardness	45 Shore A	<u>Product Characteristics</u>	
Surface	S32 Profile	Troughed Installation suitable	No
<u>Running Side</u>		Oil resistant	No
Coating Material	Fabric	Permanent antistatic	Yes
Colour		FDA approved	No
Hardness		EC 10/2011	Yes
Surface		REACH	Yes
		Flame Retardant	No
		<u>Standard Production Width</u>	3000mm

<u>Fabrication Recommendation</u>				
<u>Joining Temperature</u>	Upper	175 Celsius	<u>Heat preservation time</u>	4 min
	Lower	175 Celsius	<u>Pressure</u>	2 bar
<u>Welded Joints</u>	Single Finger			

Disclaimer

All information are recommendations and believed to be reliable, but no representations, guarantees, or warranties of any kind are made as to their accuracy or suitability for particular applications. Due to the fact that Haggart Belting has no control of use, we will not assume any liability concerning the suitability and process ability of the products mentioned herein. This also applies to defects, damages, consequential damages, and other consequences.

The information applies at approx. 20°C (68°F). Keep the belt tension to a minimum for maximum belt and conveyor life. Stated is the belt temperature. The allowable product temperature may vary.