

## Datasheet



<b>Item Code</b>	0607T16F
<b>Product Nomenclature</b>	BFab/2 EM 8-00+00(V) TR AS 1.6mm
<b>Product Group</b>	PVC-F
<b>Belt Application</b>	Food processing

<u>Product Construction</u>		<u>Technical Data</u>	
Type of fabric	EM (Polyester)	Total Thickness	1.6mm
Number of ply	2	Weight	1.6 kg/m <sup>2</sup>
Fabric feature	Lateral Stiff	Temperature Tolerance	-20 to +90 Celsius
<u>Conveying side</u>		Coeff. Friction > Steel	0,25
Coating Material		Tensile Strength at 1% elongation	6 N/mm
Colour	Transparent	Min. Pulley	30 mm
Hardness	-	<u>Product Characteristics</u>	
Surface	Fabric	Troughed Installation suitable	No
<u>Running Side</u>		Oil resistant	No
Coating Material		Permanent antistatic	Yes
Colour	Transparent	FDA approved	Yes
Hardness	-	EC 10/2011	Yes
Surface	Fabric	REACH	Yes
		Flame Retardant	No
		<u>Standard Production Width</u>	3000mm

<u>Fabrication Recommendation</u>				
<u>Jointing Temperature</u>	Upper	174 Celsius	<u>Heat preservation time</u>	4 min
	Lower	170 Celsius	<u>Pressure</u>	2 bar
<u>Welded Joints</u>	Finger Over Finger			

### Disclaimer

All information are recommendations and believed to be reliable, but no representations, guarantees, or warranties of any kind are made as to their accuracy or suitability for particular applications. Due to the fact that Haggart Belting has no control of use, we will not assume any liability concerning the suitability and process ability of the products mentioned herein. This also applies to defects, damages, consequential damages, and other consequences.

The information applies at approx. 20°C (68°F). Keep the belt tension to a minimum for maximum belt and conveyor life. Stated is the belt temperature. The allowable product temperature may vary.