

Datasheet



Item Code	0607W26F-DMU
Product Nomenclature	BFab/2 EC 6-0+0(V) W 2.6MM
Product Group	PVC-F
Belt Application	Food processing

<u>Product Construction</u>		<u>Technical Data</u>	
Type of fabric	EC (Cotton)	Total Thickness	2.6mm
Number of ply	2	Weight	2.9 kg/m ²
Fabric feature	Flexible	Temperature Tolerance	-10 to +90 Celsius
Conveying side		Coeff. Friction > Steel	0,25
Coating Material	Cotton	Tensile Strength at 1% elongation	6 N/mm
Colour	Beige	Min. Pulley	10 mm
Hardness	-	<u>Product Characteristics</u>	
Surface	-	Troughed Installation suitable	No
Running Side		Oil resistant	No
Coating Material	Cotton	Permanent antistatic	No
Colour	Beige	FDA approved	Yes
Hardness	-	EC 10/2011	Yes
Surface	Fabric	REACH	Yes
		Flame Retardant	No
		<u>Standard Production Width</u>	3000mm

<u>Fabrication Recommendation</u>				
Jointing Temperature	Upper	165 Celsius	Heat preservation time	4 min
	Lower	162 Celsius	Pressure	2 bar
Welded Joints	Finger over Finger			

Disclaimer

All information are recommendations and believed to be reliable, but no representations, guarantees, or warranties of any kind are made as to their accuracy or suitability for particular applications. Due to the fact that Haggart Belting has no control of use, we will not assume any liability concerning the suitability and process ability of the products mentioned herein. This also applies to defects, damages, consequential damages, and other consequences.

The information applies at approx. 20°C (68°F). Keep the belt tension to a minimum for maximum belt and conveyor life. Stated is the belt temperature. The allowable product temperature may vary.