

## Datasheet



<b>Item Code</b>	0756T13F
<b>Product Nomenclature</b>	BFab/2 EM 6-00+00(U) TR AS 1.3mm
<b>Product Group</b>	PU-P
<b>Belt Application</b>	Food processing

<u>Product Construction</u>		<u>Technical Data</u>	
Type of fabric	EM (Polyester)	Total Thickness	1.3mm
Number of ply	2	Weight	1.3 kg/m <sup>2</sup>
Fabric feature	Lateral Stiff	Temperature Tolerance	-20 to +90 Celsius
<u>Conveying side</u>		Coeff. Friction > Steel	0,2
Coating Material	00 Impreg. PU	Tensile Strength at 1% elongation	6 N/mm
Colour	Transparent	Min. Pulley	10 mm
Hardness	-	<u>Product Characteristics</u>	
Surface	Fabric	Troughed Installation suitable	No
<u>Running Side</u>		Oil resistant	Yes
Coating Material	00 Impreg. PU	Permanent antistatic	Yes
Colour	Transparent	FDA approved	Yes
Hardness	-	EC 10/2011	Yes
Surface	Fabric	REACH	Yes
		Flame Retardant	No
		<u>Standard Production Width</u>	3000mm

<u>Fabrication Recommendation</u>				
<u>Jointing Temperature</u>	Upper	165 Celsius	<u>Heat preservation time</u>	4 min
	Lower	162 Celsius	<u>Pressure</u>	2 bar
<u>Welded Joints</u>	Single Finger			

### Disclaimer

All information are recommendations and believed to be reliable, but no representations, guarantees, or warranties of any kind are made as to their accuracy or suitability for particular applications. Due to the fact that Haggart Belting has no control of use, we will not assume any liability concerning the suitability and process ability of the products mentioned herein. This also applies to defects, damages, consequential damages, and other consequences.

The information applies at approx. 20°C (68°F). Keep the belt tension to a minimum for maximum belt and conveyor life. Stated is the belt temperature. The allowable product temperature may vary.