

Datasheet



Item Code	0756W15C-SPT
Product Nomenclature	BFab/2 EC 8-0+0 W 1.5MM
Product Group	PU-P
Belt Application	Food processing

<u>Product Construction</u>		<u>Technical Data</u>	
Type of fabric	EC	Total Thickness	1.5mm
Number of ply	2	Weight	1.5 kg/m ²
Fabric feature	Lateral Stiff	Temperature Tolerance	-20 to +90 Celsius
<u>Conveying side</u>		Coeff. Friction > Steel	0,2
Coating Material	Cotton	Tensile Strength at 1% elongation	8N/mm
Colour	Beige	Min. Pulley	15 mm
Hardness	-	<u>Product Characteristics</u>	
Surface	-	Troughed Installation suitable	No
<u>Running Side</u>		Oil resistant	No
Coating Material	Cotton	Permanent antistatic	No
Colour	Beige	FDA approved	Yes
Hardness	-	EC 10/2011	Yes
Surface	-	REACH	Yes
		Flame Retardant	No
		<u>Standard Production Width</u>	3000mm

<u>Fabrication Recommendation</u>				
<u>Jointing Temperature</u>	Upper	175 Celsius	<u>Heat preservation time</u>	4 min
	Lower	175 Celsius	<u>Pressure</u>	2 bar
<u>Welded Joints</u>	Single Finger			

Disclaimer

All information are recommendations and believed to be reliable, but no representations, guarantees, or warranties of any kind are made as to their accuracy or suitability for particular applications. Due to the fact that Haggart Belting has no control of use, we will not assume any liability concerning the suitability and process ability of the products mentioned herein. This also applies to defects, damages, consequential damages, and other consequences.

The information applies at approx. 20°C (68°F). Keep the belt tension to a minimum for maximum belt and conveyor life. Stated is the belt temperature. The allowable product temperature may vary.