

Datasheet



Item Code	1708R13M3
Product Nomenclature	BU/2 EFS 6-00+03 RB AS M3 1.3 mm AM FL
Product Group	PU-E Frayless
Belt Application	Food processing; hydrolisis resistant, high- and low temperatures suitable, accumulation belt, higher release properties, general conveying belt;

<u>Product Construction</u>		<u>Technical Data</u>	
Type of fabric	EFS (Frayless)	Total Thickness	1.3 mm
Number of ply	2	Weight	1.4 kg/m ²
Fabric feature	Lateral Stiff	Temperature Tolerance	-30 to +120 Celsius
<u>Conveying side</u>		Coeff. Friction > Steel	0.2
Coating Material	Polyether PU	Tensile Strength at 1% elongation	6 N/mm
Colour	Royal Blue	Min. Pulley	8 mm
Hardness	92 Shore A	<u>Product Characteristics</u>	
Surface	Super Matt	Troughed Installation suitable	No
<u>Running Side</u>		Oil resistant	Yes
Coating Material	00 Impreg. PU	Permanent antistatic	Yes
Colour	Blue	FDA approved	Yes
Hardness	-	EC 10/2011	Yes
Surface	-	REACH	Yes
		Flame Retardant	No
		<u>Standard Production Width</u>	2000 mm

<u>Fabrication Recommendation</u>				
<u>Jointing Temperature</u>	Upper	162 Celsius	<u>Heat preservation time</u>	4 min
	Lower	158 Celsius		<u>Pressure</u>
<u>Welded Joints</u>	Single Finger			

Disclaimer

All information are recommendations and believed to be reliable, but no representations, guarantees, or warranties of any kind are made as to their accuracy or suitability for particular applications. Due to the fact that Haggart Belting has no control of use, we will not assume any liability concerning the suitability and process ability of the products mentioned herein. This also applies to defects, damages, consequential damages, and other consequences.
The information applies at approx. 20°C (68°F). Keep the belt tension to a minimum for maximum belt and conveyor life. Stated is the belt temperature. The allowable product temperature may vary.