

Datasheet



Item Code	2302B15YA
Product Nomenclature	BU/1 EM6 05+05 SB AM 1.5MM
Product Group	PU-E
Belt Application	Food Conveyance

<u>Product Construction</u>		<u>Technical Data</u>	
Type of fabric	EM (Polyester)	Total Thickness	1.5mm mm
Number of ply	2	Weight	1.6 kg/m2
Fabric feature	Lateral Stiff	Temperature Tolerance	-20 to +90 Celsius
<u>Conveying side</u>		Coeff. Friction > Steel	0,46
Coating Material	PU	Tensile Strength at 1% elongation	6 N/mm
Colour	SB	Min. Pulley	9 mm
Hardness	86 Shore A	<u>Product Characteristics</u>	
Surface	A Pattern	Troughed Installation suitable	Yes
<u>Running Side</u>		Oil resistant	Yes
Coating Material	PU	Permanent antistatic	Yes
Colour	SB	FDA approved	Yes
Hardness	86 Shore A	EC 10/2011	Yes
Surface	Y Pattern	REACH	Yes
		Flame Retardant	No
		<u>Standard Production Width</u>	2000mm

<u>Fabrication Recommendation</u>				
<u>Jointing Temperature</u>	Upper	165Celsius	<u>Heat preservation time</u>	3 min
	Lower	165 Celsius	<u>Pressure</u>	1.5 bar
<u>Welded Joints</u>	Single Finger			

Disclaimer

All information are recommendations and believed to be reliable, but no representations, guarantees, or warranties of any kind are made as to their accuracy or suitability for particular applications. Due to the fact that Haggart Belting has no control of use, we will not assume any liability concerning the suitability and process ability of the products mentioned herein. This also applies to defects, damages, consequential damages, and other consequences.

The information applies at approx. 20°C (68°F). Keep the belt tension to a minimum for maximum belt and conveyor life. Stated is the belt temperature. The allowable product temperature may vary.