

## Datasheet

<b>Item Code</b>	0320W24S18			
<b>Product Nomenclature</b>	BVOR/2 EM 8-00+S18 W 2.4 mm			
<b>Product Group</b>	PVC-OR			
<b>Belt Application</b>	Food grade oil resistant belt for food conveying			
<u>Product Construction</u>		<u>Technical Data</u>		
Type of fabric	EM (lateral stable)	Total Thickness	2.4 mm	
Number of ply	2	Weight	2.7 kg/m <sup>2</sup>	
Fabric feature	Lateral stable	Temperature Tolerance	-10 to +80 Celsius	
<b>Conveying side</b>		Coeff. Friction > Steel	0.25	
		Tensile Strength at 1% elongation Min. Pulley	8 N/mm 45 mm	
Coating Material	PVC-OR	<u>Product Characteristics</u>		
Colour	White	Troughed Installation suitable	No	
Hardness	70 Shore A	Oil resistant	Yes	
Surface	S18 Medium Diamond	Permanent antistatic	No	
<b>Running Side</b>		FDA approved*	Yes	
		EC 10/2011*	Yes	
Coating Material	00 Impreg. PU	REACH*	Yes	
Colour	-	Flame Retardant	No	
Hardness	-	<u>Standard Production Width</u>	3000 mm	
Surface	Fabric			
<u>Fabrication</u>				
<u>Recommendation</u>				
<b>Joining Temperature</b>	Upper	175 Celsius	<b>Heat preservation time</b>	4 min
	Lower	170 Celsius	<b>Pressure</b>	2 bar
<b>Welded Joints</b>	Finger over Finger			

\* Please see Certificate of Compliances for more details

### Disclaimer

All information are recommendations and believed to be reliable, but no representations, guarantees, or warranties of any kind are made as to their accuracy or suitability for particular applications. Due to the fact that Haggart Belting has no control of use, we will not assume any liability concerning the suitability and process ability of the products mentioned herein. This also applies to defects, damages, consequential damages, and other consequences.  
The information applies at approx. 20°C (68°F). Keep the belt tension to a minimum for maximum belt and conveyor life. Stated is the belt temperature. The allowable product temperature may vary.