

Datasheet

Item Code	0320W20G			
Product Nomenclature	BVOR/2 EM 8-00+05 W 2,0mm			
Product Group	PVC-OR			
Belt Application	Food grade oil resistant belt for food conveying			
<u>Product Construction</u>		<u>Technical Data</u>		
Type of fabric	EM (lateral stable)	Total Thickness	2,0 mm	
Number of ply	2	Weight	2,4 kg/m ²	
Fabric feature	Lateral stable	Temperature Tolerance	-10 to +80 Celsius	
Conveying side		Coeff. Friction > Steel	0,2	
		Tensile Strength at 1% elongation	8 N/mm	
Coating Material	PVC-OR	Min. Pulley	40 mm	
Colour	White	<u>Product Characteristics</u>		
Hardness	70 Shore A	Troughed Installation suitable	No	
Surface	Glossy	Oil resistant	Yes	
Running Side		Permanent antistatic	No	
		FDA approved	Yes	
Coating Material	00 Impreg. PU	EC 10/2011	Yes	
Colour	-	REACH	Yes	
Hardness	-	Flame Retardant	No	
Surface	Fabric	<u>Standard Production Width</u>	3000 mm	
<u>Fabrication</u>				
<u>Recommendation</u>				
Jointing Temperature	Upper	175 Celsius	Heat preservation time	4 min
	Lower	170 Celsius	Pressure	2 bar
Welded Joints	Finger over Finger			

* Please see Certificate of Compliances for more details

Disclaimer

All information are recommendations and believed to be reliable, but no representations, guarantees, or warranties of any kind are made as to their accuracy or suitability for particular applications. Due to the fact that Haggart Belting has no control of use, we will not assume any liability concerning the suitability and process ability of the products mentioned herein. This also applies to defects, damages, consequential damages, and other consequences. The information applies at approx. 20°C (68°F). Keep the belt tension to a minimum for maximum belt and conveyor life. Stated is the belt temperature. The allowable product temperature may vary.