

Datasheet



Item Code	0460B25M-X
Product Nomenclature	BV/2 EX 10-0+07 BK FR M2 AS 2.5 mm
Product Group	PVC-S
Belt Application	General Conveying, suitable for airport / warehouse centers

<u>Product Construction</u>		<u>Technical Data</u>	
Type of fabric	EX (low noise)	Total Thickness	2.5 mm
Number of ply	2	Weight	2.6 kg/m ²
Fabric feature	Lateral Stiff	Temperature Tolerance	-10 to +80 Celsius
<u>Conveying side</u>		Coeff. Friction > Steel	0.2
Coating Material	PVC	Tensile Strength at 1% elongation	10 N/mm
Colour	Black	Min. Pulley	50 mm
Hardness	80 Shore A	<u>Product Characteristics</u>	
Surface	Matt	Troughed Installation suitable	No
<u>Running Side</u>		Oil resistant	Yes
Coating Material	Fabric	Permanent antistatic	Yes
Colour	-	FDA approved	No
Hardness	-	EC 10/2011	No
Surface	-	REACH	Yes
		Flame Retardant	Yes
		<u>Standard Production Width</u>	3000mm

<u>Fabrication Recommendation</u>				
Jointing Temperature	Upper	175 Celsius	Heat preservation time	4 min
	Lower	170 Celsius	Pressure	2 bar
Welded Joints	Finger over Finger			

Disclaimer

All information are recommendations and believed to be reliable, but no representations, guarantees, or warranties of any kind are made as to their accuracy or suitability for particular applications. Due to the fact that Haggart Belting has no control of use, we will not assume any liability concerning the suitability and process ability of the products mentioned herein. This also applies to defects, damages, consequential damages, and other consequences.

The information applies at approx. 20°C (68°F). Keep the belt tension to a minimum for maximum belt and conveyor life. Stated is the belt temperature. The allowable product temperature may vary.