

Datasheet



Product Nomenclature	F13 S/W
Product Group Belt Application	Reoclean

<u>Product Construction</u>		<u>Technical Data</u>	
Type of fabric	Frayless	Total Thickness	1.3mm
Number of ply	1	Weight	1.6 kg/m ²
Fabric feature	Flexible	Temperature Tolerance	-20 to +90 Celsius
<u>Conveying side</u>		Coeff. Friction > Steel	0,3
Coating Material	Polyurethane	Tensile Strength at 1% elongation	6 N/mm
Colour	White	Min. Pulley	9 mm
Hardness	92 Shore A	<u>Product Characteristics</u>	
Surface	Matt	Troughed Installation suitable	No
<u>Running Side</u>		Oil resistant	Yes
Coating Material	Polyurethane	Permanent antistatic	Yes
Colour	Blue	FDA approved	Yes
Hardness	92 Shore A	EC 10/2011	Yes
Surface	Matt	REACH	Yes
		Flame Retardant	No
		<u>Standard Production Width</u>	2000mm

<u>Fabrication Recommendation</u>				
<u>Joining Temperature</u>	Upper	165 Celsius	<u>Heat preservation time</u>	4 min
	Lower	165 Celsius	<u>Pressure</u>	2 bar
<u>Welded Joints</u>	Single Finger			

Disclaimer

All information are recommendations and believed to be reliable, but no representations, guarantees, or warranties of any kind are made as to their accuracy or suitability for particular applications. Due to the fact that Haggart Belting has no control of use, we will not assume any liability concerning the suitability and process ability of the products mentioned herein. This also applies to defects, damages, consequential damages, and other consequences.

The information applies at approx. 20°C (68°F). Keep the belt tension to a minimum for maximum belt and conveyor life. Stated is the belt temperature. The allowable product temperature may vary.